



Apollo

Chandelier - Horizontal - 10 Lights

<p><u>Series</u> Apollo</p> <p><u>Product</u> Chandelier - Horizontal - 10 Lights</p> <p><u>Dimensions</u> L 57in / 145cm x W 57in / 145cm x H 41.5in / 105.4cm</p> <p><u>Weight</u> 11.2lb / 5.1kg</p> <p><u>Shipping Dimensions</u> L 51in / 129cm x W 51in / 129cm x H 26in / 66cm</p> <p><u>Shipping Weight</u> 63lb / 29kg</p> <p><u>Materials</u> Brass, Steel, Glass, White Oak</p>	<p><u>Finishes/Colors</u> Matte black metal / Brushed brass detail, Matte ivory metal / Brushed brass detail</p> <p><u>Suspension</u> Two 1/2-inch diameter stems in matching metal finish. 35in length included. 72in length available for additional cost. Stems length can be adjusted on site.</p> <p><u>Canopy</u> L 14in / 36cm x W 5in / 13cm x H 2in / 5cm solid white-oak. Available in 2 coordinating finishes: Oxidized oak for Matte black and Brushed brass metal fixtures, Whitewashed oak for Matte ivory metal fixtures.</p> <p><u>Ceiling Slope</u> 0° - 10° mounting slope. Up to 90° variable hang-straight available upon request.</p> <p><u>Certifications</u> UL/cUL (120V) CE (240V)</p>	<p><u>120V Illumination</u> Integrated LED Wattage: 45 W Lumens: 3,000 Lumens est. Color Temperature: 2700 K, 90+ CRI LED Lifetime: 50,000 Hours est. Dimming: 120V - TRIAC, ELV, 0-10V 277V - 0-10V only</p> <p><u>240V Illumination</u> Integrated LED Wattage: 45 W Lumens: 3,000 Lumens est. Color Temperature: 2700 K, 90+ CRI LED Lifetime: 50,000 Hours est. Dimming: 0-10V (DALI dimming available upon request)</p> <p><u>Driver location</u> Driver located in the canopy</p> <p><u>Fixture Mounting</u> Designed to be mounted on standard 4in. Electrical Box. Two #8-32 screws included. Additional mounting hardware provided for 240V versions.</p>
--	---	--