



Apollo

Chandelier - 2 Lights

Series
Apollo

Product
Chandelier - 2 Lights

Dimensions
L 53in/135cm x W 3in/8cm x
H 40in / 101.6cm

Shipping Dimensions
L 63in/160cm x W 19in/48cm x
H 15in/38cm

Weight
7.5lb/3.4kg

Materials
Brass, Aluminum, Glass, White Oak

Finishes/Colors
Matte black metal / Brushed brass detail,
Matte ivory metal / Brushed brass detail

Suspension
Two 1/2-inch diameter stems in match-
ing metal finish. 35in length included.
72in length available for additional cost.
Stems length can be adjusted on site.

Canopy
L 14in/36cm x W 5in/13cm x H 2in/5cm
solid white-oak. Available in 2 coordi-
nating finishes: Oxidized oak for Matte
black and Brushed brass metal fixtures.
Whitewashed oak for Matte ivory metal
fixtures.

Ceiling Slope
0° - 10° mounting slope.
Up to 90° variable hang-straight
available upon request.

Certifications
UL/cUL (120V)
CE (240V)

120/277V Illumination
Integrated LED
Wattage: 12W
Lumens: 700 Lumens est.
Color Temperature: 2700 K, 90+ CRI
LED Lifetime: 50,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

240V Illumination
Integrated LED
Wattage: 12W
Lumens: 700 Lumens est.
Color Temperature: 2700 K, 90+ CRI
LED Lifetime: 50,000 Hours est.
Dimming: 0-10V
(DALI dimming available upon request)

Driver location
Driver located in the canopy

Fixture Mounting
Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.