

Pole

04 - Surface to Floor - 3 Sections - 120V

Series
Pole

Materials
Aluminum, steel, silicone

120/277V Illumination
Integrated LED

Wattage: 8 Watts
Lumens: 300 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

Product
04 - Surface to Floor - 3 Sections - 120V

Metal Finishes
Black

Driver location
Driver located in the J-Box

Dimensions

	A	B
Min.	85in / 216cm	96in / 245cm
Preferred	87in / 221cm	94in / 239cm
Max.	89in / 226cm	92in / 234cm


Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Fixture Mounting
Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.

Weight
41.1lb/18.6kg

Wall Mount - Powered
L 5.1in/13cm x W 5.1in/13cm x
H 0.4in/1cm cylindrical plate in matching
metal finish

Certifications
UL, cUL (120V)



Pole

04 - Surface to Floor - 3 Sections - 240V

Series
Pole

Materials
Aluminum, steel, silicone

240V Illumination

Integrated LED
Wattage: 8 Watts
Lumens: 300 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 0-10V
(DALI dimming available upon request)

Product

04 - Surface to Floor - 3 Sections - 240V

Metal Finishes

Black

Driver location

Driver located in the Driver Box.

Dimensions

	A	B
Min.	85in / 216cm	96in / 245cm
Preferred	87in / 221cm	94in / 239cm
Max.	89in / 226cm	92in / 234cm

Base - Non powered

L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Wall Mount - Powered

L 4.1in/10.5cm x W 4.1in/10.5cm x
H 0.4in/1cm cylindrical plate in matching
metal finish.

Fixture Mounting

Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.

Weight


41.1lb/18.6kg

Driver Box (240V Only)

240V version includes box to house
drivers. Dimensions are L 1.2in/3cm x
W 2.9in/7.5cm x H 4.5in/11.5cm

Certification

CE (240V)



Pole

04 - Surface to Floor - 4 Sections - 120V

Series
Pole

Materials
Aluminum, steel, silicone

120/277V Illumination
Integrated LED

Product
04 - Surface to Floor - 4 Sections - 120V

Metal Finishes
Black

Wattage: 10 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

Dimensions

	A	B
Min.	122in / 310cm	116in / 295cm
Preferred	124in / 315cm	114in / 290cm
Max.	126in / 320cm	112in / 285cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)


Driver location
Driver located in the J-Box

Weight
41.6lb/18.9kg

Wall Mount - Powered
L 5.1in/13cm x W 5.1in/13cm x
H 0.4in/1cm cylindrical plate in matching
metal finish

Fixture Mounting
Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.

Certifications
UL, cUL (120V)



Pole

04 - Surface to Floor - 4 Sections - 240V

Series
Pole

Materials
Aluminum, steel, silicone

240V Illumination

Integrated LED
Wattage: 10 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: ELV or 0-10V

Product
04 - Surface to Floor - 4 Sections - 240V

Metal Finishes
Black

Driver location

Driver located in the Driver Box.

Dimensions

	A	B
Min.	122in / 310cm	116in / 295cm
Preferred	124in / 315cm	114in / 290cm
Max.	126in / 320cm	112in / 285cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Fixture Mounting


Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.

Weight
41.6lb/18.9kg

Wall Mount - Powered
L 4.1in/10.5cm x W 4.1in/10.5cm x
H 0.4in/1cm cylindrical plate in matching
metal finish.

Driver Box (240V Only)
240V version includes box to house
drivers. Dimensions are L 1.2in/3cm x
W 2.9in/7.5cm x H 4.5in/11.5cm

Certification
CE (240V)



Pole

04 - Surface to Floor - 5 Sections - 120V

Series
Pole

Materials
Aluminum, steel, silicone

120/277V Illumination
Integrated LED

Product
04 - Surface to Floor - 5 Sections - 120V

Metal Finishes
Black

Wattage: 13 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

Dimensions

	A	B
Min.	158in / 401cm	138in / 351cm
Preferred	161in / 409cm	135in / 343cm
Max.	164in / 417cm	132in / 335cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)


Driver location
Driver located in the J-Box

Weight
42.2lb/19.1kg

Wall Mount - Powered
L 5.1in/13cm x W 5.1in/13cm x
H 0.4in/1cm cylindrical plate in matching
metal finish

Fixture Mounting
Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.

Certifications
UL, cUL (120V)



Pole

04 - Surface to Floor - 5 Sections - 240V

Series
Pole

Materials
Aluminum, steel, silicone

240V Illumination

Integrated LED
Wattage: 13 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: ELV or 0-10V

Product
04 - Surface to Floor - 5 Sections - 240V

Metal Finishes
Black

Driver location

Driver located in the Driver Box.

Dimensions

	A	B
Min.	158in / 401cm	138in / 351cm
Preferred	161in / 409cm	135in / 343cm
Max.	164in / 417cm	132in / 335cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Wall Mount - Powered
L 4.1in/10.5cm x W 4.1in/10.5cm x
H 0.4in/1cm cylindrical plate in matching
metal finish.


Fixture Mounting

Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.

Weight
42.2lb/19.1kg

Driver Box (240V Only)
240V version includes box to house
drivers. Dimensions are L 1.2in/3cm x
W 2.9in/7.5cm x H 4.5in/11.5cm

Certification
CE (240V)



Pole

04 - Surface to Floor - 6 Sections - 120V

Series
Pole

Materials
Aluminum, steel, silicone

120/277V Illumination

Integrated LED
Wattage: 15 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

Product
04 - Surface to Floor - 6 Sections - 120V

Metal Finishes
Black

Dimensions

	A	B
Min.	195in / 495cm	160in / 406cm
Preferred	198in / 503cm	157in / 399cm
Max.	201in / 511cm	154in / 391cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)


Driver location
Driver located in the J-Box

Weight
42.8lb/19.4kg

Wall Mount - Powered
L 5.1in/13cm x W 5.1in/13cm x
H 0.4in/1cm cylindrical plate in matching
metal finish

Fixture Mounting
Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.

Certifications
UL, cUL (120V)



Pole

04 - Surface to Floor - 6 Sections - 240V

Series
Pole

Materials
Aluminum, steel, silicone

240V Illumination

Integrated LED
Wattage: 15 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: ELV or 0-10V

Product
04 - Surface to Floor - 6 Sections - 240V

Metal Finishes
Black

Driver location

Driver located in the Driver Box.

Dimensions

	A	B
Min.	195in / 495cm	160in / 406cm
Preferred	198in / 503cm	157in / 399cm
Max.	201in / 511cm	154in / 391cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Wall Mount - Powered
L 4.1in/10.5cm x W 4.1in/10.5cm x
H 0.4in/1cm cylindrical plate in matching
metal finish.


Fixture Mounting

Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.

Weight
42.8lb/19.4kg

Driver Box (240V Only)
240V version includes box to house
drivers. Dimensions are L 1.2in/3cm x
W 2.9in/7.5cm x H 4.5in/11.5cm

Certification
CE (240V)



Pole

04 - Surface to Floor - 7 Sections - 120V

Series
Pole

Materials
Aluminum, steel, silicone

120/277V Illumination
Integrated LED

Product
04 - Surface to Floor - 7 Sections - 120V

Metal Finishes
Black

Wattage: 18 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

Dimensions

	A	B
Min.	231in / 587cm	183in / 465cm
Preferred	235in / 597cm	179in / 455cm
Max.	239in / 607cm	175in / 445cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)


Driver location
Driver located in the J-Box

Weight
43.4lb/19.7kg

Wall Mount - Powered
L 5.1in/13cm x W 5.1in/13cm x
H 0.4in/1cm cylindrical plate in matching
metal finish

Fixture Mounting
Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.

Certifications
UL, cUL (120V)



Pole

04 - Surface to Floor - 7 Sections - 240V

Series

Pole

Materials
Aluminum, steel, silicone

240V Illumination

Integrated LED
Wattage: 18 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: ELV or 0-10V

Product

04 - Surface to Floor - 7 Sections - 240V

Metal Finishes

Black

Driver location

Driver located in the Driver Box.

Dimensions

	A	B
Min.	231in / 587cm	183in / 465cm
Preferred	235in / 597cm	179in / 455cm
Max.	239in / 607cm	175in / 445cm

Base - Non powered

L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Fixture Mounting

Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.

Weight

43.4lb/19.7kg

Wall Mount - Powered


L 4.1in/10.5cm x W 4.1in/10.5cm x
H 0.4in/1cm cylindrical plate in matching
metal finish.

Driver Box (240V Only)

240V version includes box to house
drivers. Dimensions are L 1.2in/3cm x
W 2.9in/7.5cm x H 4.5in/11.5cm

Certification

CE (240V)



Pole

04 - Surface to Floor - 8 Sections - 120V

Series

Pole

Materials
Aluminum, steel, silicone

120/277V Illumination

Integrated LED
Wattage: 20 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: 120V - TRIAC, ELV, 0-10V
277V - 0-10V only

Product

04 - Surface to Floor - 8 Sections - 120V

Metal Finishes

Black

Dimensions

	A	B
Min.	267in / 678cm	204in / 518cm
Preferred	271in / 688cm	200in / 508cm
Max.	275in / 699cm	196in / 498cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Driver location

Driver located in the J-Box

Weight

44lb/20kg

Wall Mount - Powered


L 5.1in/13cm x W 5.1in/13cm x
H 0.4in/1cm cylindrical plate in matching
metal finish

Fixture Mounting

Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.

Certifications

UL, cUL (120V)



Pole

04 - Surface to Floor - 8 Sections - 240V

Series
Pole

Materials
Aluminum, steel, silicone

240V Illumination

Integrated LED
Wattage: 20 Watts
Lumens: 400 Lumens est.
Color Temperature: 2700K, CRI: 90+
LED Lifetime: 70,000 Hours est.
Dimming: ELV or 0-10V

Product
04 - Surface to Floor - 8 Sections - 240V

Metal Finishes
Black

Driver location

Driver located in the Driver Box.

Dimensions

	A	B
Min.	267in / 678cm	204in / 518cm
Preferred	271in / 688cm	200in / 508cm
Max.	275in / 699cm	196in / 498cm

Base - Non powered
L 5.1in/13cm x W 5.1in/13cm x
H 9.9in/25.1cm cylindrical bases in
matching metal finish (appx. 35lbs)

Fixture Mounting

Designed to be mounted on standard
4in. Electrical Box.
Two #8-32 screws included.
Additional mounting hardware provided
for 240V versions.

Weight
44lb/20kg

Wall Mount - Powered
L 4.1in/10.5cm x W 4.1in/10.5cm x
H 0.4in/1cm cylindrical plate in matching
metal finish.

Driver Box (240V Only)
240V version includes box to house
drivers. Dimensions are L 1.2in/3cm x
W 2.9in/7.5cm x H 4.5in/11.5cm

Certification
CE (240V)